

**Heavy-duty overhead door holder or stop for exterior, vestibule or interior doors, either single or double acting**

**1000 SL ADJ SERIES  
SLIM LINE CONCEALED**



**STANDARD FEATURES**

- Non-handed/reversible
- Single point hold-open is field adjustable from 85° to 110°
- 5° to 7° shock compression following hold-open point
- Steel shock absorbing spring
- Maximum opening 110°, minimum door thickness 1 3/4"
- Both wood and machine screws included
- Available in all BHMA plated and sprayed finishes
- 1/2" maximum channel depth

**All Stops  
Warnock Hersey  
listed**

**WHEN ORDERING,  
please list:**

*Model number*

*Door closer number or other hardware*

*Mounting means of the door and butt size*

*Hold-open or dead-stop degree*

*Door opening and thickness*

*Finish*

**SPECIFICATIONS:**

**Stop only function to be Warnock Hersey listed as manufactured by ABH.**

*Material:  
steel/stainless steel channel 1/8" thick and 1/2" depth; arm 3/16" thick and 1" wide; jamb track 1 1/4" wide; extruded sliding block for hold-open mechanism.*

DOOR FRAME OPENING	HOLDER NUMBER	
	HOLD-OPEN	STOP
BUTTS OFFSET PIVOTS		
27" - 29 15/16"	1011SA	1021SA
30" - 35 15/16"	1012SA	1022SA
36" - 39 15/16"	1013SA	1023SA
40" - 43 15/16"	1014SA	1024SA
44" + Greater	1015SA	1025SA
BHMA NUMBER	C01511	C01541
FED. SPEC TYPE	1160	

Contact ABH for special templating or other door opening  
Average weight/unit 6 lbs.

**www.abhmfg.com**  
**E-mail: abhinfo@abhmfg.com**  
**Architectural Builders Hardware Mfg., Inc.**  
 1222 Ardmore Ave., Itasca, IL 60143  
**630.875.9900; FAX 800.9FAXABH (932.9224)**

© 2005 ABH Mfg., Inc.  
Printed in USA 02/05

