



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



# RECESSED ACCESS DOOR DW-5015

## Application

- For installation in drywall surfaces when it is required to conceal the door panel

## Product Features

- Recessed 5/8" to receive drywall
- Door flange is a textured galvanized steel tapping bead with pre-punched holes

## DW-5015 Access Door Specifications:

**Material:** Steel or Stainless Steel: 22 gage door, 22 gage mounting frame

**Door:** Recessed 5/8"

**Door Frame:** Galvanized steel drywall tapping bead on all sides

**Hinge:** Concealed

**Standard Latch:** 5/16" Square drive cam latch

**Optional Latches/Locks:** Cylinder lock and key, allen head cam latch, spanner head cam latch

**Finish:** Satin coat steel



## AVAILABLE SIZES *(Special sizes available upon request)*

NOMINAL DOOR SIZE W X H			WEIGHT PER DOOR	
inches	mm	Latches	lbs.	kg.
12 X 12	305 X 305	1	8.5	3.9
18 X 18	457 X 457	2	15	6.8
24 X 24	610 X 610	2	23	10.4
24 X 36	610 X 914	4	30	13.8

Wall or ceiling opening is  $W + 3/8"$  (9 mm)

For detailed specifications see submittal sheet

