



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



DUCT DOORS for round ducts RD-5090

Application

- Economical access to round ducts

Product Features

- Pull and catch lock system
- Gasketing on the door assures a tight seal without obstruction in the air system

RD-5090 Duct Access Door Specifications:

Door / Door Frame: 16 gauge galvanized steel

Gasketing: 1/8" thick by 1" wide closed cell neoprene

Standard Latch: Plated steel pull and catch

Finish: Mill / Aluminum

AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H			WEIGHT PER DOOR	
inches	mm	Opening	lbs.	kg.
6 X 4	150 X 100	5"	1	0.5
7 X 5	175 X 125	6"	1 1/4	0.6
8 X 6	200 X 150	7"	1 1/2	0.7
9 X 8	225 X 200	8"	1 3/4	0.8
10 X 8	250 X 200	9"	2	0.9
11 X 9	275 X 225	10"	3	1.2
13 X 10	325 X 250	12"	3 1/2	1.6
15 X 13	375 X 325	14"	4	1.8
17 X 13	425 X 325	16"	5 1/2	2.5
19 X 15	475 X 375	18"	6	2.7
19 X 17	475 X 425	20"	6 3/4	3.1
20 X 17	500 X 425	24"	7 1/4	3.3



Duct opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

