



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



UNIVERSAL FLUSH UF-5500

Application

- Installation in Drywall, Plaster, Masonry, Tile or any flush surface

Product Features

- Drawn flanged door panel with rounded corners
- Concealed hinge and welds
- Galvanized steel material with white baked on polyester powder coat

UF-5500 Access Door Specifications:

Material: 12" x 12" and smaller are 20 gauge galvanized steel door & frame.

Over 15" x 15" and larger are 18 gauge galvanized steel door & frame

Door: Flush To Frame- Drawn flanged door panel with rounded corners

Door Frame: Drawn one piece trim flange and mounting frame

Hinge: Concealed

Standard Latch: Slot Screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock and key; allen spanner or torx head cam latch

Finish: White baked on polyester powder coat



AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR		
inches	mm	Latches	lbs.	kg.
6 X 6	152 X 152	1	1.5	.68
8 X 8	203 X 203	1	2.0	.91
12 X 12	305 X 305	1	2.5	1.14
15 X 15	381 X 381	1	5.5	2.5
18 X 18	457 X 457	1	7.5	3.41
24 X 24	610 X 610	2	12.0	5.45

Wall or ceiling opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

