



**9400 Series**  
*Slim-line*  
Works with rim  
exit devices with  
a 1/2" throw  
latchbolt

**9500 Series**  
*Fire-Rated*  
Works with rim  
exit devices with  
a 3/4" throw  
latchbolt

**9600 Series**  
*Windstorm-  
Rated*  
Works with rim  
exit devices with  
a 3/4" throw  
latchbolt

**9700 Series**  
*Fire-Rated &  
Windstorm-  
Rated*  
Works with  
Corbin Russwin  
SecureBolt™  
and Yale  
SquareBolt®  
exit devices



# 9000 Family

## Surface Mounted Electric Strikes

*Sophistication*  
**Stylish Looks**

Designed with a stainless steel decorative cover  
Available in six finishes to match any decor  
Sleek lines complement ASSA ABLOY exit devices

*Convenience*  
**Easy Installation**

Completely surface mounted for quick installation  
Base and cover are separate for easy adjustments  
Field selectable fail safe/fail secure

*Quality*  
**Above and Beyond**

Exceeds Grade 1 standards for strength and performance  
Components encased in 1/2" stainless steel housing  
Independently verified above and beyond testing

ASSA ABLOY, the global leader in door opening solutions

[hesinnovations.com](http://hesinnovations.com)

# Series Options, Accessories & Specifications

## Optional Features

LBM » Latchbolt monitor

LBSM » Latchbolt  
strike monitor

## Accessories

9400/9500/9600/9700-

108 » Spacer plate  
(black or 630 finish)

9000-MTK » Metal  
template kit

SMB » Surface  
mounting box

2001M » Plug-in  
bridge rectifier

2004M » ElectroLynx  
adapter

2005M3 » SMART Pac® III

2006M » Plug-in buzzer

## Frame Application

• Metal

• Wood

## Finishes

630 » Satin stainless steel

605 » Bright brass

606 » Satin brass

612 » Satin bronze

613 » Bronze toned

613E » Dark oxidized  
satin bronze (NEW)

629 » Bright stainless steel

## Electrical

### (continuous duty)

• .45 Amps @ 12 VDC

• .26 Amps @ 24VDC



## 9400 Series

### The Easy-Install, Slim-Line, Surface Mounted Solution

#### Standard Features

- Decorative cover for a sleek look
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 500,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

#### Listings and Patents

- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev. 6) Listed
- ANSI/BHMA A156.31, Grade 1
- RoHS compliant
- Patents: 6,392,520 and 8,454,520

The 9400 Series works with rim exit devices with a 1/2" throw latchbolt



# 9500 Series

## The Strong & Durable, Fire-Rated, Surface Mounted Solution

### Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 1,500 lbs.
- Dynamic strength to 70 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

### Listings and Patents

- UL 10C fire-rated, 3 hour (fail secure only)
- CAN4-S104 (ULC-S104), NFPA-252 and ASTM-E152 fire door conformant
- UL 1034, burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev. 6) Listed
- ANSI/BHMA A156.31, Grade 1
- California Fire Marshall listed
- NFPA 80-07 compliant
- RoHS compliant
- Patents: 6,390,520, 6,392,520 and 8,454,520

The 9500 Series works with rim exit devices with a 3/4" throw latchbolt



# 9600 Series

## The Stylish, Windstorm-Rated, Surface Mounted Solution

### Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 2,000 lbs.
- Dynamic strength to 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

### Listings and Patents

- UL Listed to ANSI 250.13 Severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev.6) Listed
- ANSI/BHMA A156.31 Grade 1
- RoHs compliant
- Patents: 6,392,520 and 8,454,520

The 9600 Series works with rim exit devices with a 3/4" throw latchbolt

new



# 9700 Series Surface Mounted Electric Strike

Works with Corbin Russwin SecureBolt™ and Yale SquareBolt® exit devices

The Stylish,  
Windstorm-  
Rated and  
Fire-Rated,  
Square Bolt  
Solution

#### Standard Features

- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 2,000 lbs.
- Dynamic strength to 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

#### Listings and Patents

- UL 10C fire-rated, 3 hour (fail secure only)

- CAN4-S104 (ULC-S104), NFPA-252 and ASTM-E152 fire door conformant
- California Fire Marshall listed
- NFPA 80-07 compliant
- UL Listed to ANSI 250.13 Severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (Rev.6) Listed
- ANSI/BHMA A156.31 Grade 1
- RoHs compliant
- Patents: 6,390,520, 6,392,520 and 8,454,520



Yale SquareBolt® Exit Device

hesinnovations.com

For information call 800.626.7590 or visit us online at [www.hesinnovations.com](http://www.hesinnovations.com)

HES-056-0915