



Model 9600



# 9600 Series

## Surface Mounted Electric Strike

Works with rim exit devices with a 3/4" throw latchbolt

### Enhanced

#### Above and Beyond

Re-engineered design for greater strength and durability  
Independently verified\*  
Static strength to 2,000 lbs.  
Dynamic strength to 120 ft-lbs.  
Endurance 1,000,000 cycles

### Convenient

#### Easy Installation

Completely surface mounted for quick installation  
Base is separate from the cover making adjustments easy  
Field selectable fail safe/fail secure

### Sophistication

#### Stylish Looks

Designed with a stainless steel decorative cover  
Available in 7 finishes to match any decor  
Sleek lines complement ASSA ABLOY exit devices

The Stylish,  
Windstorm  
Rated,  
Surface  
Mounted  
Solution

ASSA ABLOY, the global leader in door opening solutions

hesinnovations.com



RIM EXIT DEVICES



FIELD SELECTABLE  
(12 OR 24VDC)



FIELD SELECTABLE  
(FAIL SECURE /  
FAIL SAFE)



GRADE 1



OUTDOOR RATED



UL 1034  
BURGLARY LISTED



ANSI A250.13-2003  
WINDSTORM  
RESISTANT



# 9600 Series

## Surface Mounted Electric Strike

### Features

#### Standard Features

- Installs in metal or wood frames
- Separate base and decorative cover for easy adjustments
- Stainless steel construction
- Static strength to 2,000 lbs.
- Dynamic strength to 120 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail secure/fail safe
- Dual voltage 12 or 24VDC
- Non-handed. Horizontal adjustability
- Five year limited warranty

#### Optional Features

- LBM** » Latchbolt monitor
- LBSM** » Latchbolt strike monitor

#### Accessories

- 9400/9500/9600-108** » Spacer plate (black or 630 finish)
- 9000-MTK** » Metal template kit
- SMB** » Surface mounting box
- 2001M** » Plug-in bridge rectifier
- 2004M** » ElectroLynx® adapter
- 2005M3** » SMART Pac® III
- 2006M** » Plug-in buzzer

#### Finishes

- 630** » Satin stainless steel
- 605** » Bright brass
- 606** » Satin brass
- 612** » Satin bronze
- 613** » Bronze toned
- 613E** » Dark oxidized satin bronze (NEW)
- 629** » Bright stainless steel

### Specifications

#### Listings and Patents

- UL listed to ANSI 250.13 severe windstorm listed
- Florida Building Code Approved (FL#14307)
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 (6th edition) listed
- ANSI/BHMA A156.31 Grade 1
- RoHS compliant
- Patents: 6,390,520; 8,454,036
- Patent Pending

#### Frame Application

- Metal
- Wood

#### Electrical (continuous duty)

- .45 Amps @ 12 VDC
- .26 Amps @ 24VDC
- PoE friendly

