

HG310 Swing Clear Hinge Guard

Standard Features

Barrel Type Hinge

.187" diameter stainless steel pin (rod)
Flanged nylon bearings
Stainless steel end pins

Material

Heavy-duty 14 gauge stainless steel

Finishes

US32D Satin Stainless Steel (630)

Standards

ANSI/BHMA Standard A156.26
Grade 1

Mounting Hardware

Fasteners concealed when door is closed
Universal screw pack provided

Capacity

Supports weights up to 600lbs.
4'0" maximum door width

Standard Sizes

6'8", 7'0", 7'2", 8'0", 10'0"

Hole Pattern

Symmetrically templated

Handing

Not required for standard 7'0", 8'0" or 10'0". Specify handing for 6'8" and 7'2" and for most optional features

Fire Rating

3 hours- hollow metal doors mounted singly
90 minutes- hollow metal and composite core wood fire doors
20 minutes- wood doors



Classified in accordance with UL10C for positive pressure



Fire-rated label

Optional Features

Finishes


US32 Bright Stainless Steel (629)
Scratch-Resistant Powder Coated Paint

Other Features

Custom lengths- specify in inches
Custom hole pattern
Dutch door hinges - suffix "DDP"
Hospital tips - suffix "HT"
Raised barrel - suffix "RB"
Special sheared leaf


Fasteners

Tamper-proof security screws
Adjust-A-Screws™ for correcting frame fit problems up to 3/8"



Tools

MTSP-100 Right angle skewdriver for ease of installation



Electrical Modifications

Current Transfer Prep (door leaf only) - suffix "CTP"

The ADA-compliant hinge is used on operating room doors to swing the door out of the opening when moving equipment in and out. The hinge guard also protects the door in the open position.

