

HG326 Swing Clear Hinge Guard

Standard Features

Barrel Type Hinge

.187" diameter stainless steel pin (rod)
 Flanged nylon bearings
 Stainless steel end pins

Material

Heavy-duty 14 gauge stainless steel

Finishes

US32D Satin Stainless Steel (630)

Standards

ANSI/BHMA Standard A156.26
 Grade 1

Mounting Hardware

Fasteners concealed when door is closed
 Universal screw pack provided

Capacity

Supports weights up to 600lbs.
 4'0" maximum door width

Standard Sizes

6'8", 7'0", 7'2", 8'0", 10'0"

Hole Pattern

Symmetrically templated

Door Edge

Specify square or beveled edge when ordering

Handing

Not required for standard 7'0", 8'0" or 10'0". Specify handing for 6'8" and 7'2" and for most optional features

Fire Rating

3 hours- hollow metal doors
 90 minutes- hollow metal and composite core wood fire doors
 20 minutes- wood doors



Classified in accordance with UL10C for positive pressure



Fire-rated label

Optional Features

Finishes


US32 Bright Stainless Steel (629)
 Scratch-Resistant Powder Coated Paint

Other Features

Custom lengths- specify in inches
 Custom hole pattern
 Dutch door hinges- suffix "DDP"
 Hospital tips - suffix "HT"
 Raised barrel - suffix "RB"
 Special sheared leaf


Fasteners

Tamper-proof security screws
 Adjust-A-Screw™ for correcting frame fit problems up to $\frac{3}{8}$ "



Tools

MTSP-100 Right angle skewdriver for ease of installation



Electrical Modifications

Current Transfer Prep - suffix "CTP"

The incorporated edge guard protects the door from unsightly dents and gouges while also protecting the hinge from vandalism.

